G5 Wrapper



Introducing the new G5 wrapper from BMG. Increased speed, efficiency, precision, and reliability.

The new BMG G5 wrapper is an automated wrapping system which utilizes servodriven jaw assembly for **faster cycle rates and increased precision**, **servo film feed**, **and fixed-length crank arms** — **eliminating the existing adjustment points that can lead to issues when adjusted improperly.** The G5 wrapper is available in various seal assembly configurations to make horizontal seals from 20" x 66" and vertical seals from 14" x 28" with an adjustable seal assembly opening of 6" to 24".

With rugged low-maintenance construction, the G5 wrapper offers modern innovation and versatility. All BMG wrappers are capable of sealing polyethylene, polyolefin, bubble, and poly mailing utilizing our patented low-temperature sealing system without the need to change parts. BMG provides custom-designed in-feeds and discharge options to meet individual requirements. From a simple hand-loaded wrapper to complete automation, including counting, collating, orienting, and case erecting/loading – BMG has a solution for you.

FEATURES

- Easier Film Threading allows for changing film rolls in record time, reducing downtime, simplifying training, and helping you keep your packaging lines running at peak efficiency
- High-speed, lighter servo-driven jaw assembly for faster cycle rates and increased precision
- Fixed-length crank arm assemblies prevent potential incorrect jaw adjustment no adjustment points needed
- Servo film feed standard
- Consistent and durable film drive system with print registration standard
- Improved / simplified controls
 for easier setup and operation
- Larger screen with intuitive UI with fault indications onscreen allowing you to identify fault causes
- Fully guarded with top dust cover standard
- BMG patented low-temperature seal system for consistent, strong seals
- Trimmed or trimless seal assemblies
- Operator and maintenance manuals via UI
- Horizontal seal lengths from 20" to 66"
- Vertical seal lengths from 14" to 28"
- Jaw assembly openings from 6" to 24"
- Scrap wind system available
- Large-capacity powered film unwind cradle



